



**BOULDIN & LAWSON, LLC**

P.O. Box 7177  
McMinnville, TN 37111  
Phone: 931-668-4090  
Toll Free : 800-443-6398  
Fax: 931-668-3209

E-mail:  
sales@bouldinlawson.com

www.bouldinlawson.com



Expanded plug on dibble unit

# Jiffy - Plug Expander and Dibble Unit



The Expander is designed to expand the jiffy plug from its dry compressed state. Trays are placed into the unit widthwise at entry point, they are both sub-irrigated and sprayed from above at progressive stages until expanded. Production rate is 12 trays per minute and water temperature is preferred to be 130 degrees (temperature can be as low as 100 degrees but expansion is at a slower rate). The plugs then pass through the optional Dibble unit where the indentations can be reformed and centered prior to seeding. Dibble unit uses B&L's quick-attach system so it can be quickly connected and always lines up correctly. It can be purchased with the Expander or at a later date if and as required.

Both units are 110V. Compressed air at 90 psi is required for the Dibble unit and a hot water supply is required for the Expander. A digital display is included to monitor the water temperature and depth adjustment for the sub-irrigation.



Before and after expansion



Dibble Unit

Options include:  
Filtered recirculation tank, heating elements in both recirc tank and expander body. This helps maintain ideal temperature and reduce water usage



Made in the USA

**BWLB&L**



A proud member of the  
**BouldinCorp™ Family**